



Escenic Content Engine
Struts Form Reference

5.3.10.154952







Copyright © 2004-2014 Vizrt. All rights reserved.

No part of this software, documentation or publication may be reproduced, transcribed, stored in a retrieval system, translated into any language, computer language, or transmitted in any form or by any means, electronically, mechanically, magnetically, optically, chemically, photocopied, manually, or otherwise, without prior written permission from Vizrt.

Vizrt specifically retains title to all Vizrt software. This software is supplied under a license agreement and may only be installed, used or copied in accordance to that agreement.

Disclaimer

Vizrt provides this publication “as is” without warranty of any kind, either expressed or implied.

This publication may contain technical inaccuracies or typographical errors. While every precaution has been taken in the preparation of this document to ensure that it contains accurate and up-to-date information, the publisher and author assume no responsibility for errors or omissions. Nor is any liability assumed for damages resulting from the use of the information contained in this document.

Vizrt’s policy is one of continual development, so the content of this document is periodically subject to be modified without notice. These changes will be incorporated in new editions of the publication. Vizrt may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time.

Vizrt may have patents or pending patent applications covering subject matters in this document. The furnishing of this document does not give you any license to these patents.

Technical Support

For technical support and the latest news of upgrades, documentation, and related products, visit the Vizrt web site at www.vizrt.com.

Last Updated

14.07.2014



Table of Contents

1 Introduction	7
2 Action Forms	9
2.1 AbstractForm	9
2.2 AbstractUserForm	9
2.3 Profiles	10
2.4 Profile	11
2.5 DefaultUserForm	12
2.6 StandardUserForm	12
2.7 LoginForm	12
2.8 PasswordForm	13
2.9 ValidateUserPasswordForm	14
2.10 ChangePasswordForm	15
2.11 DeleteProfileForm	15
2.12 SearchForm	16
2.13 ArticleSearchForm	17
2.14 SimpleSearchForm	19
2.15 AdvancedSearchForm	20
3 Actions	23
3.1 AbstractProfileAction	23
3.2 AddUserAction	23
3.3 LoginAction	24
3.4 NewPasswordAction	25
3.5 SetPasswordAction	26
3.6 AuthenticatedAction	26
3.7 AuthenticatedForwardAction	27
3.8 PopulateUserAction	28
3.9 UpdateUserAction	29
3.10 DeleteUserAction	30
3.11 DeleteProfileAction	30
3.12 LogoffAction	31
3.13 SearchAction	32





1 Introduction

This reference should contain enough information to enable a template developer to set up profile- and search-related Struts actions in an Escenic publication, so that profile/search forms may be submitted. A working knowledge of Struts is assumed.

For more on Struts, see <http://struts.apache.org>.



2 Action Forms

2.1 AbstractForm

A base class which has behaviour and properties which are common to all action forms. All action forms share the properties defined by this class.

Properties

AbstractForm inherits properties from:

- `com.escenic.tools.struts.ValidateForm`

It has no properties of its own.

2.2 AbstractUserForm

A form that collects user data needed when registering or updating a profile

The properties describes below are all settable from the html form in the jsp page.

The form contains information about the profile to create or update

Struts config

```
<form-bean
  name="com.escenic.profile.presentation.struts.AbstractUserForm"
  type="com.escenic.profile.presentation.struts.AbstractUserForm"/>
```

Action Error

This form requires that `userName` and `surName` is set. If one is missing, the user should be notified.

```
no_userName
  (On the userName property.) The userName was not specified
```

```
invalid_username
  (On the userName property.) The username did not start with a letter
```

```
no_surName
  (On the surName property.) The surName was not specified
```

AbstractUserForm inherits properties from:

- `com.escenic.profile.presentation.struts.AbstractForm`

It also has the following properties of its own:

userName
String
the username of the user

firstName
String
the firstame of the user

surName
String
the users surname

profiles
Profiles
the profiles, containing additional user information

address
String
the users address

phone
String
the users phone number

mobilePhone
String
the users mobile phone

email
String
the users email

publicationId
String
the publicationid of the profile. Returns -1 if it's a new profile

password
String
the password

id
String
the id of the profile. Returns -1 if it's a new profile

2.3 Profiles

A helper class to facilitate handling of several Profile objects. A Form may use a Profiles instance to handle lists of profiles.

Properties

Profiles inherits properties from:



- `java.lang.Object`

It also has the following properties of its own:

`item`

Profile

Returns the Profile instance given the name. It is meant to be used from a JSP page, when using Map properties: For example `form.Profiles(1).name` would refer to the name of the profile. If the item does not exist, it will be created. This method, therefore, never returns null.

`keys`

List

returns a list of keys that can be used to retrieve profiles. The List contains the names that can be used to retrieve each profile.

`size`

int

returns the total count of Profile objects

2.4 Profile

A profile related to the user

Properties

`Profile` inherits properties from:

- `java.lang.Object`

It also has the following properties of its own:

`id`

String

the id of the profile. Is -1 if the profile is not yet created

`attribute`

String

the attribute defined by the given key

`attributeNames`

Set

a set containing all the names of attributes added to the profile

`articleType`

String

the articletype of the profile

`homeSectionId`

String

the id of the homesection of the profile

2.5 DefaultUserForm

A default implementation of the AbstractUserForm

Defines that the email should be used as the username of the user

The form contains information about the user to create or update

Struts config

```
<form-bean
  name="com.escenic.profile.presentation.struts.DefaultUserForm"
  type="com.escenic.profile.presentation.struts.DefaultUserForm"/>
```

DefaultUserForm inherits properties from:

- `com.escenic.profile.presentation.struts.AbstractUserForm`

It has no properties of its own.

2.6 StandardUserForm

A standard implementation of the AbstractUserForm

Provide the same functionality as DefaultUserForm, except that this form provide a separate user name that could be anything, not just the mail-address.

The form contains information about the user to create or update

Struts config

```
<form-bean
  name="com.escenic.profile.presentation.struts.StandardUserForm"
  type="com.escenic.profile.presentation.struts.StandardUserForm"/>
```

StandardUserForm inherits properties from:

- `com.escenic.profile.presentation.struts.AbstractUserForm`

It has no properties of its own.

2.7 LoginForm

A form that collects user data needed when logging in a user

The properties describes below are all settable from the html form in the jsp page.

The form contains information about the userName and password of the user.

Struts config



```
<form-bean
  name="com.escenic.profile.presentation.struts.LoginForm"
  type="com.escenic.profile.presentation.struts.LoginForm"/>
```

Action Error

This form requires that `userName` and `password` is set. If one is missing, the user should be notified.

```
no_username
  (On the userName property.) The userName was not specified
```

```
no_password
  (On the password property.) The password was not specified
```

`LoginForm` inherits properties from:

- `com.escenic.profile.presentation.struts.AbstractForm`

It also has the following properties of its own:

```
userName
String
  the username of the user
```

```
password
String
  the users password
```

2.8 PasswordForm

A form that collects user data needed when requesting a new password

The form contains the `userName` of the user requesting a new password.

When a new password is created, the password will be available in the `password`-property of the form.

Struts config

```
<form-bean
  name="com.escenic.profile.presentation.struts.PasswordForm"
  type="com.escenic.profile.presentation.struts.PasswordForm"/>
```

Action Error

This form requires that `userName` is set. If missing, the user should be notified.

```
no_username
  (On the userName property.) The userName was not specified
```

`PasswordForm` inherits properties from:

- `com.escenic.profile.presentation.struts.AbstractForm`

It also has the following properties of its own:

password
String
 the new password of the user

userName
String
 the username of the user

2.9 ValidateUserPasswordForm

A form that collects user data needed when requesting a new password

The form contains the `userName` and `validateField` of the user requesting a new password.

When a new password is created, the password will be available in the `password`-property of the form.

The form validates that user actually is a user and that both the username and emailaddress entered is the same as the one defined in the user itself before resetting the password. If this validation is not performed, it is possible for whoever to reset a password for whoever user.

If it's required to validate another field than the emailaddress, create a new subclass and override method `protected boolean isValidField(Person p)`

Struts config

```
<form-bean
  name="com.escenic.profile.presentation.struts.ValidateUserPasswordForm"
  type="com.escenic.profile.presentation.struts.ValidateUserPasswordForm"/>
```

Action Error

This form requires that `userName` and `validateField` is set. If missing, the user should be notified.

no_username
 (On the `userName` property.) The `userName` was not specified

no_email
 (On the `validateField` property.) The `validateField` was not specified

nameAndMailDoesNotMatch
 (On the `global` property.) The `validateField` was not specified

`ValidateUserPasswordForm` inherits properties from:

- `com.escenic.profile.presentation.struts.PasswordForm`



It has no properties of its own.

2.10 ChangePasswordForm

A form that collects data needed when requesting a change of password

The form contains the old and new password

Struts config

```
<form-bean
  name="com.escenic.profile.presentation.struts.ChangePasswordForm"
  type="com.escenic.profile.presentation.struts.ChangePasswordForm"/>
```

Action Error

This form requires that both old and new password is set. If missing, the user should be notified.

`no_Password`
(On the `password` property.) The new password was not specified

`no_Old_Password`
(On the `oldPassword` property.) The old password was not specified

`ChangePasswordForm` inherits properties from:

- `com.escenic.profile.presentation.struts.AbstractForm`

It also has the following properties of its own:

`password`
String
the new password of the user

`oldPassword`
String
the oldPassword of the user

2.11 DeleteProfileForm

A form contains the name of a profile which is to be deleted

The properties describes below are all settable from the html form in the jsp page.

The form contains information about the profile to delete

Struts config

```
<form-bean
  name="com.escenic.profile.presentation.struts.DeleteProfileForm"
  type="com.escenic.profile.presentation.struts.DeleteProfileForm"/>
```

Action Error

This form requires that title is set. If missing, the user should be notified.

```
no_title
  (On the title property.) The title was not specified
```

DeleteProfileForm inherits properties from:

- `com.escenic.profile.presentation.struts.AbstractForm`

It has no properties of its own.

2.12 SearchForm

Struts config

```
<form-bean
  name="com.escenic.search.SearchForm"
  type="com.escenic.search.SearchForm"/>
```

Action Error

This are the errors returned by the validate method found on this action form.

```
errors.required
  (On the pageLength property.) when a value is missing for this property
```

```
errors.integer
  (On the pageLength property.) when the value of this property can't be
  converted to a integer
```

```
errors.minvalue
  (On the pageLength property.) when the value of this property is less or
  equal to '0'
```

```
errors.required
  (On the pageNumber property.) when a value is missing for this property
```

```
errors.integer
  (On the pageNumber property.) when the value of this property can't be
  converted to a integer
```

```
errors.minvalue
  (On the pageNumber property.) when the value of this property is smaller
  than '1'
```

```
errors.required
  (On the pageLength property.) when a value is missing for this property
```

```
errors.integer
  (On the pageLength property.) when the value of this property can't be
  converted to a integer
```



errors.minvalue

(On the `pageLength` property.) when the value of this property is less or equal to '0'

`SearchForm` inherits properties from:

- `com.escenic.tools.struts.ValidateForm`

It also has the following properties of its own:

pageLength

String

The number of search hits to show on each result page.; default value=10

pageNumber

String

the page in the search result we want to display.; default value=1

searchEngineName

String

The name of the search engine to use for search. When no name is given the default search engine configured by the system will be used.; default value='null'

publicationId

String

The publication to search; default value='null'

2.13 ArticleSearchForm

This is the abstract super class of all article search forms.

Struts config

```
<form-bean
  name="com.escenic.search.ArticleSearchForm"
  type="com.escenic.search.ArticleSearchForm"/>
```

Action Error

This are the errors returned by the validate method found on this action form.

errors.integer

(On the `includeSectionId` property.) when the value of this property can't be converted to a integer

errors.required

(On the `includeSubSections` property.) when a value is missing for this property

errors.integer

(On the `excludeSectionId` property.) when we are not able to produce a Integer.

errors.required

(On the `maxRows` property.) when a value is missing for this property

errors.integer

(On the `maxRows` property.) when the value of this property can't be converted to a integer

errors.required

(On the `optimized` property.) when a value is missing for this property

`ArticleSearchForm` inherits properties from:

- `com.escenic.search.SearchForm`

It also has the following properties of its own:

includeSectionId**String[]**

The list over sections that is to be included. The list is made up of Strings that can be converted to Integers.

includeSubSections**String**

Should we include sub sections in the search.; default value=false

excludeSectionId**String[]**

The list over sections that is to be excluded. The list is made up of Strings that can be converted to Integers.

articleType**String[]**

The Array of article types to be included in the search.; default value=an empty array, meaning that all article types is to be included

sortString**String**

The String used for deciding the sort order.; default value=an empty String.

sortStrings**List**

A list used to prepopulate the `sortString` properties. The list contains all legal values for the `sortString` property.

descending**String**

Should we sort decending or ascending.



maxRows

String

the number of rows to return from the database.; default value=-1

searchType

String

the search type

searchTypes

List

A list used to prepopulate the searchType properties. The list contains all legal values for the searchType property.

optimized

String

the optimized property

stemType

String

the stem type property

stemTypes

List

A list used to prepopulate the stemType properties. The list contains all legal values for the stemType property.

2.14 SimpleSearchForm

This is the search action form to use when you want to create a simple search.

Struts config

```
<form-bean
  name="simpleSearchForm"
  type="com.escenic.search.SimpleSearchForm"/>
```

Action Error

This are the errors returned by the validate method found on this action form.

errors.required

(On the **searchString** property.) when a value is missing for this property

SimpleSearchForm inherits properties from:

- **com.escenic.search.ArticleSearchForm**

It also has the following properties of its own:

`searchString`
String
 the string used when searching

2.15 AdvancedSearchForm

This is the search action form to use when you want to create a advanced search page.

Struts config

```
<form-bean
  name="advancedSearchForm"
  type="com.escenic.search.AdvancedSearchForm"/>
```

Action Error

This are the errors returned by the validate method found on this action form.

`errors.required`
 (On the `searchExpression` property.) when a value is missing for this property

`errors.required`
 (On the `startDay` property.) when a value is missing for this property

`errors.integer`
 (On the `startDay` property.) when the value of this property can't be converted to a integer

`errors.range`
 (On the `startDay` property.) when the value of this property is not between '1' and '31'

`errors.required`
 (On the `startMonth` property.) when a value is missing for this property

`errors.integer`
 (On the `startMonth` property.) when the value of this property can't be converted to a integer

`errors.range`
 (On the `startMonth` property.) when the value of this property is not between '0' and '11'

`errors.required`
 (On the `startYear` property.) when a value is missing for this property

`errors.integer`
 (On the `startYear` property.) when the value of this property can't be converted to a integer

**errors.range**

(On the **startYear** property.) when the value of this property is not between '0' and '{@link Integer#MAX_VALUE}'

errors.date

(On the **fromDate** property.) when we are not able to produce a date.

errors.required

(On the **toDay** property.) when a value is missing for this property

errors.integer

(On the **toDay** property.) when the value of this property can't be converted to a integer

errors.range

(On the **toDay** property.) when the value of this property is not between '1' and '31'

errors.required

(On the **toMonth** property.) when a value is missing for this property

errors.integer

(On the **toMonth** property.) when the value of this property can't be converted to a integer

errors.range

(On the **toMonth** property.) when the value of this property is not between '0' and '11'

errors.required

(On the **toYear** property.) when a value is missing for this property

errors.integer

(On the **toYear** property.) when the value of this property can't be converted to a integer

errors.range

(On the **toYear** property.) when the value of this property is not between '0' and '11'

errors.date

(On the **toDate** property.) when we are not able to produce a date.

AdvancedSearchForm inherits properties from:

- **com.escenic.search.ArticleSearchForm**

It also has the following properties of its own:

all (read/write)**String**

All the words written here must be present in the article to get a hit.

exactPhrase (read/write)**String**

All words written here will be searched for as a phrase.

atLeastOne (read/write)**String**

At least one of these words must be present.

without (read/write)**String**

These words must NOT be present.

startDay (read/write)**String**

The day on which to start searching; default value=1

startMonth (read/write)**String**

The month on which to start searching; default value=0

startYear (read/write)**String**

The year on which to start searching; default value=current year

toDay (read/write)**String**

The day on which to stop searching; default value=1

toMonth (read/write)**String**

The month on which to stop searching; default value=0

toYear (read/write)**String**

The year on which to stop searching; default value=0

days (read-only)**List**

A list used to prepopulate the startDay and toDay properties. The list contains all values in the range from '1' to '31'. Both 'label' and 'value' is the number representation of the day of the month.

months (read-only)**List**

A list used to prepopulate the startMonth and toMonth properties. The list contains all values in the range from '0' to '11'. Both 'label' and 'value' is the number representation of the month of the year.

years (read-only)**List**

A list used to prepopulate the startYear and toYear properties. The list contains all values in the range from '1990' to 'currentYear'. Both 'label' and 'value' is the number representation of the year.

3 Actions

3.1 AbstractProfileAction

A base class which has behaviour and properties which are common to all actions

It requires an AbstractForm and is responsible for forwarding the request to the appropriate forward according to the result of the action.

If the action is a success, it forwards to the targetUrl, if defined, or success.

If the action fails, the request is forwarded to errorUrl, if defined, or input page

Struts config

```
<action path="/some/path/AbstractProfileAction"
  type="com.escenic.profile.presentation.struts.AbstractProfileAction"
  name=""
  input="/some/path/AbstractProfileAction-input.jsp"
  validate="true">
</action>
```

Action Forwards

3.2 AddUserAction

Creates a new user in escenic based on the values defined in the form. It creates both the user and profiles

Struts config

```
<action path="/newUser"
  type="com.escenic.profile.presentation.struts.AddUserAction"
  name="UserForm"
  input="/newUser-input.jsp"
  validate="true">

  <forward name="success"
    path="/newUser-success.jsp"/>
</action>
```

Action Form

This action can be used with the following form:

`com.escenic.profile.presentation.struts.AbstractUserForm`
The form containing the userdata

Action Forwards

input page

If the user couldn't be created.

success

If the user was successfully created

Action Error

If creating the user fails, an error will be logged, and the action will be forwarded to the input-page.

create_user_failed

(On the `global` property.) If creating user failes

3.3 LoginAction

Logs a user in to escenic

Struts config

```
<action path="/login"
  type="com.escenic.profile.presentation.struts.LoginAction"
  name="LogonForm"
  input="/login-input.jsp"
  validate="true">

  <forward name="success"
    path="/login-success.jsp"/>
</action>
```

Action Form

This action can be used with the following form:

`com.escenic.profile.presentation.struts.LoginForm`

The form contains information about the username and password to use when performing a login

Action Forwards

input page

If the user couldn't be logged in

success

If login was successfull.



Action Error

If login fails, an error will be logged and the action will be forwarded to the input-page and the user should be notified about what went wrong.

`login_failed`

(On the `global` property.) If logon fails

`login_failed_other`

(On the `global` property.) If logon fails due to unforeseen events

`login_failed_account_expired`

(On the `global` property.) If logon fails due to an expired account

3.4 NewPasswordAction

Resets the password of the given user

Struts config

```
<action path="/newPassword"
  type="com.escenic.profile.presentation.struts.NewPasswordAction"
  name="PasswordForm"
  input="/newPassword-input.jsp"
  validate="true">

  <forward name="success"
    path="/newPassword-success.jsp"/>
</action>
```

Action Form

This action can be used with the following form:

`com.escenic.profile.presentation.struts.PasswordForm`

The form contains information about the user which requires a new password

Action Forwards

`input page`

If the password couldn't be reset

`success`

If reset was a success.

Action Error

If resetting password fails, an error will be logged, and the action will be forwarded to the input-page.

`reset_password_failed`
 (On the `global` property.) If resetting password failes

3.5 SetPasswordAction

Resets the password of the current user. This can only be done in a logged-in context

Struts config

```
<action path="/setPassword"
  type="com.escenic.profile.presentation.struts.SetPasswordAction"
  name="ChangePasswordForm"
  input="/setPassword-input.jsp"
  validate="true">

  <forward name="success"
    path="/setPassword-success.jsp"/>
</action>
```

Action Form

This action can be used with the following form:

`com.escenic.profile.presentation.struts.ChangePasswordForm`
 The form contains information about the new password

Action Forwards

input page

If the password couldn't be updated

success

If update was a success.

Action Error

If updating password fails, an error will be logged, and the action will be forwarded to the input-page.

`set_password_failed`
 (On the `global` property.) If updating password failes

3.6 AuthenticatedAction

Some actions, such as for instance updating a users profile, should be done in context of a logged in user.

This action is an abstract superclass which ensures that a user is logged in before being able to perform the requested task. Subclasses needs to



implement one method, `performAuthenticated`, to take advantage of user authentication.

The action ensures that the user is logged in before invoking the abstract method `performAuthenticated` which performs the requested action.

The abstract method `performAuthenticated` obeys the same contract as `Action#execute`.

Struts config

```
<action path="/doSomethingAuthenticated"
  type="com.escenic.profile.presentation.struts.AuthenticatedAction"
  name="SomeForm"
  input="/doSomethingAuthenticated-input.jsp"
  validate="true">

  <forward name="success"
    path="/doSomethingAuthenticated-success.jsp"/>
</action>
```

Action Forwards

input page

not-logged-in if the user was not logged in

success

If user is authenticated.

3.7 AuthenticatedForwardAction

This action ensures the user is logged in before forwarding the request to the success-mapping. If the user is not logged in, the user will be forwarded to "not-logged-in" mapping

Struts config

```
<action path="/doSomethingAuthenticated"
  type="com.escenic.profile.presentation.struts.AuthenticatedForwardAction"
  name="com.escenic.tools.struts.ForwardForm"
  input="/doSomethingAuthenticated-input.jsp"
  validate="true">

  <forward name="success"
    path="/doSomethingAuthenticated-success.jsp"/>
</action>
```

Action Forwards

input page

not-logged-in if the user was not logged in

success

If user is authenticated.

3.8 PopulateUserAction

Populates a form with data of the currently logged in user. This action does not lock the user when loaded.

Struts config

```
<action path="/populateUser"
  type="com.escenic.profile.presentation.struts.PopulateUserAction"
  name="UserForm"
  input="/populateUser-input.jsp"
  validate="true">

  <forward name="success"
    path="/populateUser-success.jsp"/>

  <forward name="not-logged-in"
    path="/populateUser-not-logged-in.jsp"/>
</action>
```

Action Form

This action can be used with the following form:

```
com.escenic.profile.presentation.struts.AbstractUserForm
  The form is populated with data from the user
```

Action Forwards
input page

If the user couldn't be loaded.

success

If the user was successfully loaded

not-logged-in

If user is not logged in

Action Error

If loading the user fails, an error will be logged, and the action will be forwarded to the input-page.

user_error

(On the `global` property.) If loading user fails

3.9 UpdateUserAction

Updates the logged in user with the values defined in the form. It both updates existing profiles and creates new profiles if user has added a new profile. The userName will not be updated using this action as this is a readonly value.

Struts config

```
<action path="/updateUser"
  type="com.escenic.profile.presentation.struts.UpdateUserAction"
  name="UserForm"
  input="/updateUser-input.jsp"
  validate="true">

  <forward name="success"
    path="/updateUser-success.jsp"/>

  <forward name="not-logged-in"
    path="/updateUser-not-logged-in.jsp"/>
</action>
```

Action Form

Below is a list of the Action Forms known to work with this Action. All of these Action Forms is a instance of {@link AbstractUserForm}.

DefaultUserForm

Implementation which uses the email as username.

StandardUserForm

Implementation which uses a separate field as username.

Action Forwards

input page

If the user couldn't be updated.

success

If the user was successfully updated

not-logged-in

If user is not logged in

Action Error

If updating the user fails, an error will be logged, and the action will be forwarded to the input-page.

update_user_failed

(On the `global` property.) If updating user failes

3.10 DeleteUserAction

Deletes the current user. The user will also be logged out of escenic as the user no longer has an available account.

Struts config

```
<action path="/deleteUser"
  type="com.escenic.profile.presentation.struts.DeleteUserAction"
  name=""
  input="/deleteUser-input.jsp"
  validate="true">

  <forward name="success"
    path="/deleteUser-success.jsp"/>

  <forward name="not-logged-in"
    path="/deleteUser-not-logged-in.jsp"/>
</action>
```

Action Forwards

input page

If the user couldn't be deleted.

success

If the user was successfully deleted

not-logged-in

If user is not logged in

Action Error

If deleting the user fails, an error will be logged, and the action will be forwarded to the input-page.

could_not_delete_user

(On the `global` property.) If deleting user fails

3.11 DeleteProfileAction

Deletes a named profile from current user

Struts config

```
<action path="/deleteProfile"
  type="com.escenic.profile.presentation.struts.DeleteProfileAction"
  name=""
  input="/deleteProfile-input.jsp"
  validate="true">
```



```
<forward name="success"
  path="/deleteProfile-success.jsp"/>

<forward name="not-logged-in"
  path="/deleteProfile-not-logged-in.jsp"/>
</action>
```

Action Forwards

input page

If the profile couldn't be deleted.

success

If the profile was successfully deleted

not-logged-in

If user is not logged in

Action Error

If deleting the profile fails, an error will be logged, and the action will be forwarded to the error page.

couldNotFindProfile

(On the `global` property.) If the profile to delete could not be found

couldNotDeleteProfile

(On the `global` property.) If the profile couldn't be deleted

3.12 LogoffAction

Logs off currently logged in user. The session will still be valid, but the user will no longer be able to do authenticated actions

Struts config

```
<action path="/logoff"
  type="com.escenic.profile.presentation.struts.LogoffAction"
  name="LogoffForm"
  input="/logoff-input.jsp"
  validate="true">

  <forward name="success"
    path="/logoff-success.jsp"/>
</action>
```

Action Form

This action can be used with the following form:

```
com.escenic.profile.presentation.struts.LogoffForm
  Contains forwarding information
```

Action Forwards

success
If logoff was a success

3.13 SearchAction

This is the component that does the actual search. The Search Action component will work with different Action forms. The only requirement is that all action forms are an instance of the Search Form class.

To provide a simple and an advanced search will you need to configure the SearchAction class twice in struts-config.xml. One for each form you will use.

Struts config

```
<action path="/search/simple"
  type="com.escenic.search.SearchAction"
  name="simpleSearchForm"
  input="/search/simple-input.jsp"
  validate="true">

  <forward name="success"
    path="/search/simple-success.jsp"/>
</action>
```

Action Form

Below is a list of the Action Forms known to work with this Action. All of these Action Forms is a instance of SearchForm.

com.escenic.search.SearchForm
This is the Abstract Super class for all SearchForms.

com.escenic.search.SimpleSearchForm
Use this Action Form when you want to create a simple search.

com.escenic.search.AdvancedSearchForm
Use this Action Form when you want to create a advanced search.

Action Forwards

This is a list of the action forwards used by this Action.

input page

When an error or something that requires the system to give the user a message, is the input parameter used. This forward can be overridden by providing a value for the 'input' property on the Action Form.



success

This forward is used when we have a result to display. Even a empty result is a result. This forward can be overridden by providing a value for the 'result' property on the Action Form.

Request attribute

The following request attributes are made available on the forwarded page.

result

This attribute is of type `com.escenic.search.ResultPage`. The list of hits for this search.

Action Error

This is a list of the errors that can be created by this action.

errors.form

(On the `ActionErrors.GLOBAL_ERROR` property.) When the Action Form provided is of the wrong type. {0} represents the provided Action Form, {1} the expected type.