

Escenic Widget Framework  
**Core Widgets Tag Reference**

3.1.2.161056



# Table of Contents

<a href="#">1 Introduction</a> .....	5
<a href="#">2 wf-core Tag Library</a> .....	6
<a href="#">2.1 wf-core:exists</a> .....	6
<a href="#">2.2 wf-core:findFragmentItem</a> .....	6
<a href="#">2.3 wf-core:getArticleSummariesInGroup</a> .....	7
<a href="#">2.4 wf-core:getRssFeed</a> .....	7
<a href="#">2.5 wf-core:mapCSS</a> .....	8
<a href="#">2.6 wf-core:resolveConfigSections</a> .....	8
<a href="#">2.7 wf-core:resolveWireframe</a> .....	8
<a href="#">2.8 wf-core:stripHTML</a> .....	9
<a href="#">2.9 wf-core:getFileTypeStyleClass</a> .....	9
<a href="#">2.10 wf-core:getEventOccurrenceListMap</a> .....	10
<a href="#">2.11 wf-core:getArticlesInGroup</a> .....	11
<a href="#">2.12 wf-core:getPicturesInGroup</a> .....	11
<a href="#">2.13 wf-core:getTaggedArticleIdList</a> .....	12
<a href="#">2.14 wf-core:getCurtailedText</a> .....	12
<a href="#">2.15 wf-core:getGroupByName</a> .....	13
<a href="#">2.16 wf-core:getArticlesInList</a> .....	13
<a href="#">2.17 wf-core:getArticleFieldsMap</a> .....	14
<a href="#">2.18 wf-core:getPresentationPool</a> .....	14
<a href="#">2.19 wf-core:listSkins</a> .....	15
<a href="#">2.20 wf-core:generatePageURL</a> .....	15
<a href="#">2.21 wf-core:iterateViews</a> .....	15
<a href="#">2.22 wf-core:image</a> .....	16
<a href="#">2.23 wf-core:renderFragment</a> .....	17
<a href="#">2.24 wf-core:countArticleComments</a> .....	17
<a href="#">2.25 wf-core:evalField</a> .....	18
<a href="#">2.26 wf-core:getCaptchaCustomHTML</a> .....	18
<a href="#">2.27 wf-core:getConfigSectionPool</a> .....	18
<a href="#">2.28 wf-core:getFieldValueByKey</a> .....	19
<a href="#">2.29 wf-core:getTagCloud</a> .....	19
<a href="#">2.30 wf-core:getVideoPreviewImageUrl</a> .....	20
<a href="#">2.31 wf-core:getYouTubeVideoUrl</a> .....	20
<a href="#">2.32 wf-core:include</a> .....	21

<a href="#">2.33 wf-core:includeESI</a>	21
<a href="#">2.34 wf-core:isVideoArticle</a>	22
<a href="#">2.35 wf-core:notPresent</a>	22
<a href="#">2.36 wf-core:present</a>	22
<a href="#">2.37 wf-core:renderContext</a>	23
<a href="#">2.38 wf-core:renderItemsInArea</a>	23
<a href="#">2.39 wf-core:showItems</a>	23
<a href="#">2.40 wf-core:view</a>	24
<a href="#">2.41 wf-core:widgetAjaxMarkup</a>	24
<a href="#">2.42 wf-core:pageFragment</a>	24
<a href="#">2.43 wf-core:iteratorView</a>	25
<a href="#">3 wf-functions Tag Library</a>	26
<a href="#">3.1 wf-functions:getRssSource</a>	26
<a href="#">3.2 wf-functions:getTweetsForURL</a>	26
<a href="#">3.3 wf-functions:getCaptchaHTML</a>	26
<a href="#">3.4 wf-functions:convertFahrenheitToCelsius</a>	26
<a href="#">3.5 wf-functions:getRelativeDate</a>	27
<a href="#">3.6 wf-functions:getDateObject</a>	27
<a href="#">3.7 wf-functions:getDateString</a>	27
<a href="#">3.8 wf-functions:getTermFromTagIdentifier</a>	28
<a href="#">3.9 wf-functions:getImageDimension</a>	28
<a href="#">3.10 wf-functions:parseFeedForImage</a>	28
<a href="#">3.11 wf-functions:getConfigSectionByInheritance</a>	28
<a href="#">3.12 wf-functions:isContainedInList</a>	29
<a href="#">3.13 wf-functions:getImageRepresentation</a>	29
<a href="#">3.14 wf-functions:getSuitableRepresentation</a>	29
<a href="#">3.15 wf-functions:isFieldAccessible</a>	30
<a href="#">3.16 wf-functions:getDateDifference</a>	30
<a href="#">3.17 wf-functions:handleLineBreaks</a>	30
<a href="#">3.18 wf-functions:isValidName</a>	30
<a href="#">3.19 wf-functions:isNumeric</a>	31
<a href="#">3.20 wf-functions:filterArticleList</a>	31
<a href="#">3.21 wf-functions:getSubList</a>	31
<a href="#">3.22 wf-functions:getTopicURL</a>	31
<a href="#">3.23 wf-functions:matchFileExtension</a>	32
<a href="#">3.24 wf-functions:getDescBreakpointsAsList</a>	32
<a href="#">3.25 wf-functions:getDefaultAspectVariant</a>	32

<a href="#">3.26 wf-functions:getArticleSummary</a>	32
<a href="#">3.27 wf-functions:findGroupName</a>	33
<a href="#">3.28 wf-functions:generatePageURLWithoutQueryString</a>	33
<a href="#">3.29 wf-functions:isImageContent</a>	33
<a href="#">3.30 wf-functions:getRelativeTime</a>	34
<a href="#">3.31 wf-functions:getClientTypeDefinition</a>	34
<a href="#">3.32 wf-functions:getImageSizes</a>	34
<a href="#">3.33 wf-functions:hasLazyFragment</a>	34
<a href="#">4 wf-util Tag Library</a>	35
<a href="#">4.1 wf-util:wrap</a>	35
<a href="#">4.2 wf-util:link</a>	35
<a href="#">5 Deprecated Tags</a>	37

# 1 Introduction

This manual contains reference information about various tag library Escenic used by Widget Framework. It contains only reference information about those tags which are used by core widgets, and assumes you have a general understanding of the Widget Framework and how it works. Specifically, you should at least have read the **Widget Framework User Guide**. If you are going to modify those tags or create new tag , then you also need to have a good understanding of both JSP and java.

The manual is primarily intended to be used by template developers who will used these tags to develop new widgets/templates.

## 2 wf-core Tag Library

This library contains widget framework core tags. These tags are used in the framework and various widgets. Widgets used these tags to fetch contents, perform business logic and render html.

### 2.1 wf-core:exists

This tag checks whether a particular controller, view, template exist or not.

#### Syntax

```
<wf-core:exists
    id="..."
    path="..."?
    scope="..."?
    type="..."?
    view="..."?
    widgetName="..."?/>
```

#### Attributes

##### **id, mandatory**

Names the scripting variable created by this tag, as well as the key value used to locate the bean added to the specified scope.

##### **type**

##### **widgetName**

Specify widget name for which you are looking a particular controller or view or index.jsp file exist or not

##### **path**

This attribute contains path of the file which this tag will check.

##### **view**

View name which you are looking for

##### **scope**

Specify in which scope result will be set

### 2.2 wf-core:findFragmentItem

This tag returns the PresentationElement that matches with given fragment token. This tag is used for lazy loading of page fragments.

#### Syntax

```
<wf-core:findFragmentItem
    fragmentToken="..."
    var="..."/>
```

#### Attributes

**var, mandatory**

Result will be returned in that variable

**fragmentToken, mandatory**

Fragment token that will be matched. Each element in the config section pool will be searched for this token.

## 2.3 wf-core:getArticleSummariesInGroup

This tag reads article summaries from a group

### Syntax

```
<wf-core:getArticleSummariesInGroup
    contentType="..."?
    group="..."
    max="..."?
    scope="..."?
    var="..."/>
```

### Attributes

**var, mandatory**

In the content studio we can create group under an area and in the group we can place various content items. This tag will read article summaries of content items for the given group. If there is multiple content type item you can filter item also.

**group, mandatory**

the group name for which article summaries will be read

**contentType**

Filter content item by content type

**max**

Define how many items you want to fetch

**scope**

Specify in which scope result will be set

## 2.4 wf-core:getRssFeed

Will fetch RSS feed from specified URL.

### Syntax

```
<wf-core:getRssFeed
    id="..."
    maxArticles="..."?
    scope="..."?
    sourceUrls="..."/>
```

### Attributes

**id, mandatory**

The name of the attribute that will contain the list of feed entries

**sourceUrls, mandatory**

URLs from which feed will be fetched.

**maxArticles, mandatory**

Limits how many feed will be fetched

**scope**

Specify in which scope fetched feed will be set

## 2.5 wf-core:mapCSS

This tag will read css mappings from **CssMappingResources.properties** file.

### Syntax

```
<wf-core:mapCSS
    fileNamePrefix="...."
    scope="...."?
    var="...."/>
```

### Attributes

**var, mandatory**

Names the scripting variable created by this tag, as well as the key value used to locate the bean added to the specified scope.

**fileNamePrefix, mandatory**

Prefix of the properties file name from which mapping will be read

**scope**

Specify in which scope result will be set

## 2.6 wf-core:resolveConfigSections

This tag defines which config section will be used for a section or article page. It follows inheritance to find out the correct config page.

### Syntax

```
<wf-core:resolveConfigSections/>
```

## 2.7 wf-core:resolveWireframe

This tag used to identify which wireframe will be used. If nothing is specified in the parameter then **default** wireframe will be used.

### Syntax

```
<wf-core:resolveWireframe
```

```
scope="..."?
var="..."/>
```

## Attributes

**var, mandatory**

**scope**

## 2.8 wf-core:stripHTML

Remove all HTML tags from given input string.

### Syntax

```
<wf-core:stripHTML
  id="..."
  maxLength="..."?
  scope="..."?
  value="..."/>
```

## Attributes

**id, mandatory, no runtime expressions**

The name of the attribute that will contain output string

**value, mandatory**

The input string that may content HTML tags

**maxLength**

Maximum length of the output string.

**scope**

Specify in which scope result will be set

## 2.9 wf-core:getFileTypeStyleClass

This tag gets file type style class names for related media files from their mime-types.

### Syntax

```
<wf-core:getFileTypeStyleClass
  fileMimeType="..."?
  relatedObject="..."
  var="..."/>
```

## Attributes

**var, mandatory, no runtime expressions**

The name of the attribute that will contain output string

**relatedObject, mandatory**

The object which mime-type is searched for class name.

**fileMimeType**

The mime-type of the related file.

## 2.10 wf-core:getEventOccurrenceListMap

This tag creates a list of events within given time frame.

### Syntax

```
<wf-core:getEventOccurrenceListMap
    articleType="..."?
    id="..."
    max="..."?
    numberOfHours="..."?
    publicationName="..."?
    range="..."?
    scheduleFieldName="..."?
    sortOrder="..."?
    sortString="..."?
    tagFieldName="..."?
    tagIdentifiers="..."?/>
```

### Attributes

**id, mandatory, no runtime expressions**

This is the object where the result will be placed.

**range, mandatory**

Events within this range will be listed.

**max**

Maximum size of the list will be determined by this attribute.

**tagIdentifiers**

Events that have this tags are included in the result. If tagIdentifiers is not given, all events included.

**tagFieldName**

This name is used to query on solr for events.

**numberOfHours**

Events that will happen within this hour will be listed.

**publicationName**

This specifies from which publication, events have to fetch.

**articleType**

This attribute sets the content type of article to be listed.

**scheduleFieldName**

The name of the schedule field in solr index (which is derived from the name of the field in content-type definition).

**sortOrder**

This specifies the list sorting order whether this is ascending or descending.

**sortString**

This specifies on which field the results will be sorted.

## 2.11 wf-core:getArticlesInGroup

This tag lists all the articles in the mentioned group.

### Syntax

```
<wf-core:getArticlesInGroup
    contentType="..."
    group="..."
    max="..."?
    var="..."/>
```

### Attributes

**var, mandatory, no runtime expressions**

This is the object where the results will be placed.

**group, mandatory**

The group name from where articles have to fetch.

**contentType, mandatory**

This denotes which type of articles have to fetch.

**max**

This denotes the maximum number of the articles to be fetched.

## 2.12 wf-core:getPicturesInGroup

This tag lists all the pictures in the mentioned group.

### Syntax

```
<wf-core:getPicturesInGroup
    contentType="..."?
    group="..."
    includeArticleRelatedPictures="..."?
    max="..."?
    var="..."/>
```

### Attributes

**var, mandatory, no runtime expressions**

This is the object where the results will be placed.

**group, mandatory**

The group name from where pictures have to fetch.

**contentType**

This denotes which type of pictures have to fetch.

**max**

This denotes the maximum number of the articles to be fetched.

**includeArticleRelatedPictures**

This denotes whether to include related picture or not.

## 2.13 wf-core:getTaggedArticleIdList

This tag lists all the tagged article ids.

### Syntax

```
<wf-core:getTaggedArticleIdList
    articleTypes="..."?
    id="..."
    max="..."
    publicationName="..."?
    sectionId="..."?
    sortOrder="..."?
    sortString="..."?
    startIndex="..."
    tagFieldName="..."
    tagIdentifiers="..."/>
```

### Attributes

**id, mandatory, no runtime expressions**

This is the object where the result will be placed.

**tagIdentifiers, mandatory**

This is tag name.

**tagFieldName, mandatory**

This is tag schema name.

**max, mandatory**

Maximum number or article to fetch.

**startIndex, mandatory**

Starting index of the list.

**sortString**

The list will be sorted with respect to this string.

**sectionId**

Id of the section.

**publicationName**

Name of the publication.

**articleTypes**

Which type of article to fetch.

**sortOrder**

Determine the sorting order (ascending or descending).

## 2.14 wf-core:getCurtailedText

This tag is used to crop a input text to a given length.

### Syntax

```
<wf-core:getCurtailedText
    ellipsis="..."?>
```

```
inputText="...."
maxLength="...."
var="...."/>
```

## Attributes

**var, mandatory, no runtime expressions**

This is the object where the result will be placed.

**inputText, mandatory**

Input text that has to be crop to a certain length.

**maxLength, mandatory**

The length of the output text.

**ellipsis**

The tailing text of the output text.

## 2.15 wf-core:getGroupName

This tag gets the group as a PresentationElement object from the group name.

### Syntax

```
<wf-core:getGroupName
  areaName="...."
  groupName="...."
  pool="...."?
  var="...."/>
```

## Attributes

**var, mandatory, no runtime expressions**

This is the object where the result will be placed.

**groupName, mandatory**

Name of the group which will be searched.

**areaName, mandatory**

The name of the area where the group is located.

**pool**

The active PresentationPool object.

## 2.16 wf-core:getArticlesInList

This tag reads articles from a list of a section.

### Syntax

```
<wf-core:getArticlesInList
  contentType="...."
  listName="...."
  max="...."?
  var="...."/>
```

## Attributes

### **var, mandatory, no runtime expressions**

This is the object where the result will be placed.

### **listName, mandatory**

This is the list name from where the articles have to be fetched.

### **contentType, mandatory**

This attribute tells which type of contents to be fetched.

### **max**

This attribute tells maximum number of articles to be fetched.

## 2.17 wf-core:getArticleFieldsMap

This tag is used to make a map with the widget fields of all panels.

## Syntax

```
<wf-core:getArticleFieldsMap
    articleTypeName="...."?
    content="...."
    publicationId="...."
    var="...."/>
```

## Attributes

### **articleTypeName**

**Deprecated.** Usage of this attribute should be removed.

### **publicationId, mandatory**

This attribute is used to specify the publication.

### **content, mandatory**

This sets the article from which the value have to be fetched.

### **var, mandatory, no runtime expressions**

This is the object where the results will be placed.

## 2.18 wf-core:getPresentationPool

This tag gets the current presentation pool object.

## Syntax

```
<wf-core:getPresentationPool
    section="...."?
    var="...."/>
```

## Attributes

### **var, mandatory, no runtime expressions**

This is the object where the result will be placed.

**section**

The current section object.

## 2.19 wf-core:listSkins

This tag will return available skins. Basically this tag will check available top level directories under the skin directory of publication. It will treat those top level directories as skin.

### Syntax

```
<wf-core:listSkins
    id="..." />
```

### Attributes

**id, mandatory**

Names the scripting variable created by this tag, as well as the key value used to locate the bean added to the specified scope.

## 2.20 wf-core:generatePageURL

This tag will generate page URL from the existing page URL and parameters supplied as attribute to the tag.

### Syntax

```
<wf-core:generatePageURL
    parameters="..." ?
    var="..." />
```

### Attributes

**var, mandatory, no runtime expressions**

The variable where the generated page URL value will be stored.

**parameters**

A map of parameters to be added as query string to the generated URL.

## 2.21 wf-core:iterateViews

This tag iterates through a map of views to select a particular one for each item in a list of articles.

### Syntax

```
<wf-core:iterateViews
    items="..."
    selectableViewMap="..."
    var="..."
    varIndex="..." ?>
    ...
```

```
</wf-core:iterateViews>
```

## Attributes

### **var, mandatory, no runtime expressions**

The scripting variable through which the selected view is exposed in **page** scope.

### **items, mandatory**

A list of teaser items, a view is to be selected for each item in the list.

### **selectableViewMap, mandatory**

The map of selectable views.

### **varIndex, no runtime expressions**

A scripting variable that if set, can be used to access the index of the current item to be rendered by the selected view.

## 2.22 wf-core:image

This tag will create an img element with appropriate image representation.

## Syntax

```
<wf-core:image
    alt="...."?
    article="...."?
    articleId="...."?
    articleTypeName="...."?
    aspectVariant="...."?
    imagePolicy="...."?
    onClick="...."?
    preload="...."?
    scale="...."?
    styleClass="...."?
    title="...."?
    width="...."?/>
```

## Attributes

### **articleId**

The id of the image article.

### **article**

The image article.

### **width**

The width of the image.

### **alt**

The alternate text of the image.

### **title**

The title of the image.

### **scale**

The image scale.

**articleTypeName**

**Deprecated.** The type of the article.

**styleClass**

Style class name of the image.

**onClick**

**Deprecated.** The onclick handler of the image.

**imagePolicy**

The image policy.

**aspectVariant**

The aspect variant.

**preload**

The preload attribute. Possible values are proxy, placeholder

## 2.23 wf-core:renderFragment

Renders a page fragment based on its loading policy. If loading policy selected for a page fragment is **onPage**, this tag will execute its body content. However, if **lazy** is selected as loading policy, a placeholder HTML fragment will replace the actual page fragment.

### Syntax

```
<wf-core:renderFragment
    element="...">
    ...
</wf-core:renderFragment>
```

### Attributes

**element, mandatory**

The **neo.xredsys.presentation.PresentationElement** for which the page fragment is to be loaded based on the loading policy.

## 2.24 wf-core:countArticleComments

This tag counts the number of comments of a Article.

### Syntax

```
<wf-core:countArticleComments
    article="..."?
    articleId="..."?
    topLevelOnly="..."?
    var="...">
    ...
</wf-core:countArticleComments>
```

### Attributes

**var, mandatory, no runtime expressions**

Result is returned via this attribute

**articleId, no runtime expressions**

This id will be used to fetch the article which comments are to be counted. If this is not given, this tag tries to find an 'article' object in the requestScope and calculates the number of comments for that article.

**article, no runtime expressions**

If this attribute is given, comments of this PresentationArticle article object is counted as result.

**topLevelOnly, no runtime expressions**

If this attribute is set to true, this tag only calculates the number of top level comments.

## 2.25 wf-core:evalField

This tag takes the content-type field data as input and searches for bean properties.

### Syntax

```
<wf-core:evalField
    id="..."
    inputFieldValue="...">
    ...
</wf-core:evalField>
```

### Attributes

**id, mandatory**

This is the object where result be will placed.

**inputFieldValue, mandatory**

This is the input field data of content-type as String. The tag will search for this property in the bean.

## 2.26 wf-core:getCaptchaCustomHTML

This generates custom html code for captcha.

### Syntax

```
<wf-core:getCaptchaCustomHTML>
    ...
</wf-core:getCaptchaCustomHTML>
```

## 2.27 wf-core:getConfigSectionPool

This tag resolves the **PresentationPool** for the current config section.

### Syntax

```
<wf-core:getConfigSectionPool>
  ...
</wf-core:getConfigSectionPool>
```

## 2.28 wf-core:getFieldValueByKey

This tag returns the value of field determined by key.

### Syntax

```
<wf-core:getFieldValueByKey
  articleContent="..."?
  articleId="..."?
  articleSummary="..."?
  key="..."?
  var="...">
  ...
</wf-core:getFieldValueByKey>
```

### Attributes

#### **var, mandatory, no runtime expressions**

Result is returned via this attribute.

#### **articleSummary**

If this attribute is present, the field value will be retrieved from the summary.

#### **articleContent**

If **articleSummary** attribute is not present and this attribute is present, then the field value will be retrieved from the article.

#### **articleId**

If **articleSummary** or **articleContent** attribute is absent, and this attribute is present, the field value will be retrieved from the article that has this id.

#### **key, mandatory**

The key for which the value is to be retrieved.

## 2.29 wf-core:getTagCloud

Generates tag cloud.

### Syntax

```
<wf-core:getTagCloud
  id="..."
  max="..."?
  minimumFrequency="..."?
  sortCriteria="..."?
  sortOrder="..."?
  tagStructureName="...">
  ...
</wf-core:getTagCloud>
```

## Attributes

### **id, mandatory**

Result is returned via this attribute.

### **tagStructureName, mandatory**

The name of the tag structure

### **sortCriteria, mandatory**

Sort criteria for the tag cloud, allowed values are **alphabetical**, **ranking**, and **random**.

### **sortOrder**

Sort order for the tag cloud, allowed values are **ascending** and **descending**.

### **max**

Maximum number of tags to be included.

### **minimumFrequency**

Minimum frequency count for each tag.

## 2.30 wf-core:getVideoPreviewImageUrl

Gets the video preview image URL for a video article.

## Syntax

```
<wf-core:getVideoPreviewImageUrl
    articleId="..."
    imageVersion="..."?
    relationTypeName="..."
    var="...">
    ...
</wf-core:getVideoPreviewImageUrl>
```

## Attributes

### **var, mandatory, no runtime expressions**

Result is returned via this attribute.

### **articleId, mandatory**

The id of the video article.

### **relationTypeName, mandatory**

The **relation-type** name of the preview image.

### **imageVersion**

The image version for which the URL will be retrieved.

## 2.31 wf-core:getYouTubeVideoUrl

This tag retrieves the URL of a Youtube video.

## Syntax

```
<wf-core:getYouTubeVideoUrl
    embeddedUrl="..."
```

```

var="...."
videoCode="....">
...
</wf-core:getYouTubeVideoUrl>
```

## Attributes

### **var, mandatory, no runtime expressions**

Result is returned via this attribute.

### **videoCode, mandatory**

The code of the Youtube video.

### **embeddedUrl, mandatory**

If this attribute is set, the embedded video URL will be retrieved.

## 2.32 wf-core:include

Renders a widget.

## Syntax

```

<wf-core:include
    elementWidth="...."?
    widgetElement="...."?
    widgetName="...."?>
...
</wf-core:include>
```

## Attributes

### **widgetName, no runtime expressions**

Name of the widget

### **widgetElement, no runtime expressions**

Widget presentation element

### **elementWidth, no runtime expressions**

Width of widget container

## 2.33 wf-core:includeESI

Renders a template inside an ESI block.

## Syntax

```

<wf-core:includeESI
    templateFile="....">
...
</wf-core:includeESI>
```

## Attributes

**templateFile, mandatory, no runtime expressions**

Template file to include.

## 2.34 wf-core:isVideoArticle

Determines if a given article is a video article or not.

### Syntax

```
<wf-core:isVideoArticle
    articleContent="..."?
    articleId="..."?
    articleSummary="..."?
    var="...">
    ...
</wf-core:isVideoArticle>
```

### Attributes

**var, mandatory, no runtime expressions**

Result is returned via is this attribute.

**articleSummary**

An article summary to check if it is a video article.

**articleContent**

An article to check if it is a video article.

**articleId**

The id of an article to check if it is a video article.

## 2.35 wf-core:notPresent

### Syntax

```
<wf-core:notPresent
    name="...">
    ...
</wf-core:notPresent>
```

### Attributes

**name, no runtime expressions**

The name of the widget to look for.

## 2.36 wf-core:present

Determines if a widget is defined in a publication or not.

### Syntax

```
<wf-core:present  
    name="...">  
    ...  
</wf-core:present>
```

## Attributes

### **name, no runtime expressions**

The name of the widget to look for.

## 2.37 wf-core:renderContext

Renders the template of the root group in the current config pool.

## Syntax

```
<wf-core:renderContext>  
    ...  
</wf-core:renderContext>
```

## 2.38 wf-core:renderItemsInArea

Renders the templates of the items in a given area.

## Syntax

```
<wf-core:renderItemsInArea  
    areaName="..."  
    elementwidth="..."?>  
    ...  
</wf-core:renderItemsInArea>
```

## Attributes

### **areaName, mandatory**

The name of the area for which the items are to be rendered.

### **elementwidth**

The width of the element container.

## 2.39 wf-core:showItems

Renders the templates of a list of items found in the request scope.

## Syntax

```
<wf-core:showItems  
    level="..."?>  
    ...  
</wf-core:showItems>
```

## Attributes

### **level**

Defines the nesting limit for the items to be rendered.

## 2.40 wf-core:view

Renders a view of a widget.

### Syntax

```
<wf-core:view
    flush="..."?
    view="..."?
    widget="..."?
    widgetName="..."?>
    ...
</wf-core:view>
```

## Attributes

### **widget**

The widget article for which the view is to be rendered.

### **widgetName**

The name of the widget for which the view is to be rendered.

### **view**

The name of the view to render.

### **flush**

If this attribute is set, the buffer will be flushed.

## 2.41 wf-core:widgetAjaxMarkup

This tag prints the link containing URL for ajax loading of the widget.

### Syntax

```
<wf-core:widgetAjaxMarkup>
    ...
</wf-core:widgetAjaxMarkup>
```

## 2.42 wf-core:pageFragment

Generates page holder fragments for lazily loaded items.

### Syntax

```
<wf-core:pageFragment
    element="...">
    ...
</wf-core:pageFragment>
```

```
</wf-core:pageFragment>
```

## Attributes

### **element, mandatory**

A lazily loaded element for which the page holder fragment will be generated.

## 2.43 wf-core:iteratorView

This tag iterates through a map of views to select a particular one for each item in a list of articles.

## Syntax

```
<wf-core:iteratorView
    resultItems="..." 
    selectableView="...">
    ...
</wf-core:iteratorView>
```

## Attributes

### **selectableView, mandatory**

The map of selectable views.

### **resultItems, mandatory**

A list of teaser items, a view is to be selected for each item in the list.

## 3 wf-functions Tag Library

This library contains widget framework functions tags.

### 3.1 wf-functions:getRssSource

#### Syntax

```
| wf-functions:getRssSource(java.lang.String)
```

**Return type:** `java.lang.String`

**Method executed**

[com.escenic.framework.tag.util.EWFUtil:getRssSource\(java.lang.String\)](#)

### 3.2 wf-functions:getTweetsForURL

#### Syntax

```
| wf-functions:getTweetsForURL(java.lang.String,java.lang.String)
```

**Return type:** `java.util.List`

**Method executed**

[com.escenic.framework.tag.util.EWFUtil:getTweetsForURL\(java.lang.String,java.lang.String\)](#)

### 3.3 wf-functions:getCaptchaHTML

#### Syntax

```
| wf-functions:getCaptchaHTML()
```

**Return type:** `java.lang.String`

**Method executed**

[com.escenic.framework.tag.util.EWFUtil:getCaptchaHTML\(\)](#)

### 3.4 wf-functions:convertFahrenheitToCelsius

#### Syntax

```
| wf-functions:convertFahrenheitToCelsius(int, boolean)
```

**Return type:** `java.lang.Number`

**Method executed**

```
com.escenic.framework.tag.util.EWFUtil:convertFahrenheitToCelsius\(int, boolean\)
```

## 3.5 wf-functions:getRelativeDate

**Syntax**

```
| wf-functions:getRelativeDate(java.util.Date, long)
```

**Return type:** `java.util.Date`

**Method executed**

```
com.escenic.framework.tag.util.EWFUtil:getRelativeDate\(java.util.Date, long\)
```

## 3.6 wf-functions:getDateObject

**Syntax**

```
| wf-functions:getDateObject(java.lang.String)
```

**Return type:** `java.util.Date`

**Method executed**

```
com.escenic.framework.tag.util.EWFUtil:getDateObject\(java.lang.String\)
```

## 3.7 wf-functions:getDateString

**Syntax**

```
| wf-functions:getDateString(java.lang.String)
```

**Return type:** `java.lang.String`

**Method executed**

```
com.escenic.framework.tag.util.EWFUtil:getDateString\(java.lang.String\)
```

## 3.8 wf-functions:getTermFromTagIdentifier

### Syntax

```
wf-functions:getTermFromTagIdentifier(java.lang.String, java.lang.String)
```

**Return type:** `java.lang.String`

### Method executed

[`com.escenic.framework.tag.util.EWFUtil:getTermFromTagIdentifier\(java.lang.String, java.lang.String\)`](#)

## 3.9 wf-functions:getImageDimension

### Syntax

```
wf-functions:getImageDimension(java.lang.String)
```

**Return type:** `java.util.Map`

### Method executed

[`com.escenic.framework.tag.util.EWFUtil:getImageDimension\(java.lang.String\)`](#)

## 3.10 wf-functions:parseFeedForImage

### Syntax

```
wf-functions:parseFeedForImage(java.lang.String)
```

**Return type:** `java.lang.String`

### Method executed

[`com.escenic.framework.tag.util.EWFUtil:parseFeedForImage \(java.lang.String\)`](#)

## 3.11 wf-functions:getConfigSectionByInheritance

### Syntax

```
wf-functions:getConfigSectionByInheritance(neo.xredsys.api.Section, java.lang.String, int)
```

**Return type:** `neo.xredsys.api.Section`

**Method executed**

```
com.escenic.framework.tag.util.EWFUtil:getConfigSectionByInheritance\(neo.xredsys.api.Se  
java.lang.String, int\)
```

## 3.12 wf-functions:isContainedInList

**Syntax**

```
wf-functions:isContainedInList(java.util.List,java.lang.Object)
```

**Return type: boolean****Method executed**

```
com.escenic.framework.tag.util.EWFUtil:isContainedInList\(java.util.List,java.lang.Object\)
```

## 3.13 wf-functions:getImageRepresentation

**Syntax**

```
wf-  
functions:getImageRepresentation(java.lang.String,neo.xredsys.api.Publication,java.lang.String)
```

**Return type: java.lang.String****Method executed**

```
com.escenic.framework.tag.util.EWFUtil:  
getImageRepresentation\(java.lang.String,neo.xredsys.api.Publication,java.lang.String\)
```

## 3.14 wf-functions:getSuitableRepresentation

**Syntax**

```
wf-  
functions:getSuitableRepresentation(java.lang.String,neo.xredsys.api.Publication,java.lang.String,jav
```

**Return type: java.lang.String****Method executed**

```
com.escenic.framework.tag.util.EWFUtil:  
getSuitableRepresentation\(java.lang.String,neo.xredsys.api.Publication,java.lang.String\)
```

### 3.15 wf-functions:isFieldAccessible

**Syntax**

```
| wf-functions:isFieldAccessible(int,java.lang.String,java.lang.String)
```

**Return type:** boolean**Method executed**

[com.escenic.framework.tag.util.EWFUtil:isFieldAccessible\(int,java.lang.String,java.lang.String\)](#)

### 3.16 wf-functions:getDateDifference

**Syntax**

```
| wf-functions:getDateDifference(java.util.Date,java.util.Date)
```

**Return type:** java.lang.String**Method executed**

[com.escenic.framework.tag.util.EWFUtil:getDateDifference\(java.util.Date,java.util.Date\)](#)

### 3.17 wf-functions:handleLineBreaks

**Syntax**

```
| wf-functions:handleLineBreaks(java.lang.String)
```

**Return type:** java.lang.String**Method executed**

[com.escenic.framework.tag.util.EWFUtil:handleLineBreaks\(java.lang.String\)](#)

### 3.18 wf-functions:isValidName

**Syntax**

```
| wf-functions:isValidName(java.lang.String)
```

**Return type:** boolean**Method executed**

[com.escenic.framework.tag.util.EWFUtil:isValidName\(java.lang.String\)](#)

### 3.19 wf-functions:isNumeric

**Syntax**

```
| wf-functions:isNumeric(java.lang.String)
```

**Return type:** boolean**Method executed**

[com.escenic.framework.tag.util.EWFUtil:isNumeric\(java.lang.String\)](#)

### 3.20 wf-functions:filterArticleList

**Syntax**

```
| wf-functions:filterArticleList(java.util.Collection,java.lang.String,java.lang.String)
```

**Return type:** java.util.List**Method executed**

[com.escenic.framework.tag.util.EWFUtil:filterArticleList\(java.util.Collection,java.lang.](#)

### 3.21 wf-functions:getSubList

**Syntax**

```
| wf-functions:getSubList(java.util.List,java.lang.String,java.lang.String)
```

**Return type:** java.util.List**Method executed**

[com.escenic.framework.tag.util.EWFUtil:getSubList\(java.util.List,java.lang.String,java.](#)

### 3.22 wf-functions:getTopicURL

**Syntax**

```
| wf-functions:getTopicURL(java.lang.String,java.lang.String,java.lang.String)
```

**Return type:** java.lang.String**Method executed**

[com.escenic.framework.tag.util.EWFUtil:getTopicURL\(java.lang.String,java.lang.String,java.lang.String\)](#)

## 3.23 wf-functions:matchFileExtension

### Syntax

```
wf-
functions:matchFileExtension(neo.xredsys.presentation.PresentationArticle,java.lang.String)
```

**Return type:** boolean

### Method executed

[com.escenic.framework.tag.util.EWFUtil:matchFileExtension\(neo.xredsys.presentation.Presen](#)

## 3.24 wf-functions:getDescBreakpointsAsList

### Syntax

```
wf-functions:getDescBreakpointsAsList(java.lang.String[])
```

**Return type:** java.util.ArrayList

### Method executed

[com.escenic.framework.tag.util.EWFUtil:getDescBreakpointsAsList\(java.lang.String\[\]\)](#)

## 3.25 wf-functions:getDefaultAspectVariant

### Syntax

```
wf-functions:getDefaultAspectVariant()
```

**Return type:** java.lang.String

### Method executed

[com.escenic.framework.tag.util.EWFUtil:getDefaultAspectVariant\(\)](#)

## 3.26 wf-functions:getArticleSummary

### Syntax

```
wf-functions:getArticleSummary(int)
```

**Return type:** java.lang.String

**Method executed**

[com.escenic.framework.tag.util.EWFUtil:getArticleSummary\(int\)](#)

## 3.27 wf-functions:findGroupByName

**Syntax**

```
wf-functions:findGroupByName(neo.xredsys.presentation.PresentationPool,  
java.lang.String,int)
```

**Return type:** neo.xredsys.presentation.PresentationElement

**Method executed**

[com.escenic.framework.tag.util.EWFUtil:  
findGroupByName\(neo.xredsys.presentation.PresentationPool,  
java.lang.String,int\)](#)

## 3.28 wf-functions:generatePageURLWithoutQueryString

**Syntax**

```
wf-functions:generatePageURLWithoutQueryString(javax.servlet.http.HttpServletRequest)
```

**Return type:** java.lang.String

**Method executed**

[com.escenic.framework.tag.util.EWFUtil:generatePageURLWithoutQueryString\(javax.servlet.](#)

## 3.29 wf-functions:isImageContent

**Syntax**

```
wf-functions:isImageContent(neo.xredsys.presentation.PresentationArticle)
```

**Return type:** boolean

**Method executed**

[com.escenic.framework.tag.util.EWFUtil:isImageContent\(neo.xredsys.presentation.Presentat](#)

### 3.30 wf-functions:getRelativeTime

**Syntax**

```
| wf-functions:getRelativeTime(java.util.Date)
```

**Return type:** `java.util.Map`**Method executed**

[com.escenic.framework.tag.util.EWFUtil:getRelativeTime\(java.util.Date\)](#)

### 3.31 wf-functions:getClientTypeDefinition

**Syntax**

```
| wf-functions:getClientTypeDefinition(neo.xredsys.api.Section)
```

**Return type:** `com.escenic.common.util.JSONMap`**Method executed**

[com.escenic.framework.tag.util.EWFUtil:getClientTypeDefinition\(neo.xredsys.api.Section\)](#)

### 3.32 wf-functions:getImageSizes

**Syntax**

```
| wf-functions:getImageSizes(int)
```

**Return type:** `java.util.Set`**Method executed**

[com.escenic.framework.tag.util.EWFUtil:getImageSizes\(int\)](#)

### 3.33 wf-functions:hasLazyFragment

**Syntax**

```
| wf-functions:hasLazyFragment(neo.xredsys.presentation.PresentationElement)
```

**Return type:** `boolean`**Method executed**

[com.escenic.framework.tag.util.EWFUtil:hasLazyFragment\(neo.xredsys.presentation.PresentationElement\)](#)

## 4 wf-util Tag Library

This library contains widget framework utility tags.

### 4.1 wf-util:wrap

#### Syntax

```
<wf-util:wrap
    htmlTag="..."?
    styleClass="..."?
    widgetName="..."?>
    ...
</wf-util:wrap>
```

#### Attributes

##### **htmlTag, mandatory**

The HTML tag to wrap with.

##### **styleClass**

The value of 'class' attribute

##### **widgetName**

Specify widget name for which you are looking a particular controller or view or index.jsp file exist or not

### 4.2 wf-util:link

#### Syntax

```
<wf-util:link
    click="..."?
    loadingDevices="..."?
    showLink="..."?
    styleClass="..."?
    url="..."?>
    ...
</wf-util:link>
```

#### Attributes

##### **url**

The url where the page should redirect to.

##### **click**

The onclick event for the link.

##### **showLink, mandatory**

Whether to render the link element or not.

**styleClass**

The value of 'class' attribute

**loadingDevices**

The devices on which inline loading will be enabled.

## 5 Deprecated Tags

Following is a list of tags marked as deprecated.

- `getPaginationRange.tag`, use Search Component widget.
- `getSearchResult.tag`, use Search Component widget.
- `getSearchResultLink.tag`, use Search Component widget.
- `getTagSearchResult.tag`, use Teaser widget.
- `getTeaserImageMap.tag`, use Teaser widget.
- `getTeaserImageMapList.tag`, use Teaser widget.
- `iteratorView.tag`, use `wf-core:iterateViews` tag.
- `pageFragment.tag`, use `wf-core:renderFragment` tag.

It is highly recommended to replace these tags with the suggested functionality. In some future version of Widget Framework, these tags might be removed.